

كونتينتال الزيوت وزيوت التزييت مرم ح Continental Oils & Lubricants F.Z.E.

PRODUCT DATA SHEET

BRAX HYDRAULIC 150

Description

BRAX HYDRAULIC oils are high performance oils designed to provide outstanding oxidation and water separation protection for most general industrial bearing and circulating oil system applications and certain other industrial applications which do not requires oils with extreme pressure additive.

Benefits:

- Rust protection superior or equivalent to the best premium quality conventional hydraulic oil.
- Good water separation.
- Excellent oxidation resistance.
- Anti-corrosion and anti-foaming capability
- Enhanced demulsibility and excellent water separation properties
- Low pour point

Application:

- Suitable for most plain and rolling elements bearings and general industrial applications.
- Low or moderately loaded enclosed gears where EP performance is not required.

Performance Standards:

Morgan lubrications specifications DIN 51524 parts 2 DENISON HF 1A, CINCINNATI MACHINE P 62, AFNOR NFE 48600 HL, ISO-L-HL DIN 51517 -1- TYPE C DIN 51517-1-TYPE CL



كونتيننتال الزيوت وزيوت التزييت مرمح Continental Oils & Lubricants F.Z.E.

CONTEX HYDRAULIC OIL 150

Typical Properties:

Particulars	ASTM METHOD	ISO 150
Color	D-1500	Light Yellow
Density @ 15 ° C, kg/L	D-1298	0.890
Viscosity @ 40 ° C cSt	D-445	150
Viscosity @ 100 ° C cSt	D-445	15
Viscosity Index	D-2270	95
Flash Point (COC) ⁰ C	D-92	266
Rust Test Distilled water	D-665A	Pass